

MODELS:

RTB 153

Throughput : 2.5 to 3.5 t/h

Power supply : 6,70 to 7,10 kW

Grader : EAC 153 3 screens ø 630 mm



RTB 354

Throughput : 3.5 to 5 t/h

Power supply : 8,25 to 9,70 kW

Grader : EAC 354 4 screens ø 630 mm



RTB 355

Throughput : 4 to 8 t/h

Power supply : 8,25 to 9,70 kW

Grader : EAC 355 5 grilles ø 630 mm



PL 355

Throughput : 4 to 8 t/h

Power supply : 8,25 to 9,70 kW

Grader : EAC 355 5 screens ø 630 mm



RTPL 704

Throughput: 6 to 15 t/h

Power supply: 10,10 to 16,40 kW

Grader : EAC 704 4 screens ø 805 mm



MOBILE SEED PROCESSING PLANT ROAD MODEL



Professional

Since 1985, DOREZ manufactures Mobile Seed Processing Plants, **reliable and robust** for **all type of seeds** as wheat, barley, oat, peas, horse beans, soya, osr, rice, flax...

DESCRIPTION OF OUR MACHINES :

- A **TRAILER** with 2 axes on suspension an inertia brake, built in our factory for a perfect assembly of the differents components. The trailer received an EC certification category O2 and our factory is certi-fied to do it.
- A **ROTARY GRADER MAROT** well-known for its strong **ASPIRATION** which has a densimetric effect. The dust is collected by a cyclone considerably over-sized to don't slow down the air flow from the grader. The **SCREENS** has the highest perforation index of the market. (nb of holes/m²). The grader MAROT provides a constant Thousand Grain Weight.
- **2 special elevators** design for a smooth handling of the seeds, full emptying (for the varietal purity). The first one feeds the grader and has a folding hopper for a quick implementation. The second carries the graded grains to the seed treater.
- A **SEED TREATER** treats proportionally the seeds with the slurry. (the machine can be either meca-nic or electronic)
- **Waste CENTRALIZATION** with a screw below the grader and the cyclone for a packaging either in bags, big-bags or in bulk with a pallet conveyor hydraulically adjustable in height (standard: unloading only at the right of the machine; in option right or left).
- An **Elevator** for treated seeds installed at the end of the seed treater on a revolving turret, adjustable in height with an hydraulic jack. It has accessories to do bags, big-bags or loading in bulk in a trailer.



PROTECTION OF THE OPERATOR AND ENVIRONMENT

- **Retention tank** below each recipient with chemicals.
- **Ventilation** dedicated for contaminated dust and vapour (option).
- **Hand washing** tank.
- **Contaminated rinse water collection** with electronic injection (option), re-use afterwards.

QUICK IMPLEMENTATION FOR THE COMFORT OF THE OPERATOR

- **Hydraulic stands** for a quick flat level of the machine
- **FOLDING HOPPER** at the rear
- **ROTATING** rear elevator
- Waste unloading either at the **RIGHT or LEFT** (OPTION)
- Winding **50m** of electric cable
- **Quick emptying** of the elevators and convenient « **cleaning** » of the grain circuit



LEFT Position



CENTRAL Position



RIGHT Position



LEFT waste conveyor (BULK) ▲



RIGHT waste conveyor (BIG-BAG) ►

